

CLAIMS

1. An improved hole saw boss including a threaded member adapted to accommodate at least two hole saws of different cutting diameters.
2. An improved hole saw boss including:
5 a threaded member incorporating at least a first and second threaded portion; said first threaded portion adapted to engage a threaded bore of a first hole saw; and said second threaded portion adapted to engage a threaded bore of a second hole saw, wherein the cutting diameter of said first hole saw is different to the cutting diameter of said second hole saw.
- 10 3. An improved hole saw boss of claim 2 wherein said second hole saw cutting diameter is smaller than said first hole saw cutting diameter.
4. An improved hole saw boss of claim 2 wherein said boss includes a base member to which the threaded member is connected.
- 15 5. An improved hole saw boss of claim 2 wherein said threaded member incorporates a first threaded portion and at least one other threaded portion of stepped down diameter to accommodate hole saws of different threaded bore diameters.
6. An improved hole saw boss of claim 2 wherein said first and second threaded portion diameters correspondingly engage with commonly available hole saw threaded bore diameters.
- 20 7. An improved hole saw boss of claim 2 wherein at least one threaded portion is of a length capable of accommodating more than one hole saw of different cutting diameters.
8. An improved hole saw boss of claim 2 wherein said base member and said threaded member include a central aperture adapted to allow a drill bit to fit there through.
- 25 9. An improved hole saw boss of claim 2 wherein said boss includes a connection means which is configured to engage a mandrel.
10. An improved hole saw boss of claim 2 wherein said second hole saw is chosen to fit snugly within an existing aperture of a work piece.
- 30 11. An improved hole saw boss of claim 10 wherein said first hole saw is adapted to drill a hole larger than the existing hole into said work piece.

12. An improved hole saw boss of claim 2 wherein the cutting surface of said second hole saw extends beyond the cutting face of said first hole saw.

5 13. An improved hole saw boss of claim 10 wherein said cutting surface of said second hole saw contacts the planar face of said work piece before said cutting surface of said first hole saw.

10 14. An improved hole saw boss including:
a threaded member adapted to accommodate at least two hole saws of different cutting diameters;
a base member having at least one notch; and
at least one drive pin, said drive pin configured to engage both said at least one notch on said base member and an existing aperture on at least one of said hole saws.

15. An improved hole saw boss of claim 14 wherein said at least one drive pin is magnetised to restrain said drive pin within said aperture on said hole saw.